

ERSKINE[®]
ATTACHMENTS LLC

www.erskineattachments.com
800.437.6912

SOIL CONDITIONER SKID STEER ATTACHMENT

**TILL, LEVEL AND
CONDITION...**



This attachment has all of the benefits of our Utility Soil Conditioner, plus a unique floating connection that provides automatic leveling as the unit follows the contour of the ground. Easily rake stones and debris to either side or straight ahead for easy pickup. Achieve greater ground speed with the large-diameter rotor and aggressive teeth that pulverize the soil on the go. The counter-rotating rotor action moves soil ahead while tilling. This allows you to fill in low spots and cut down high spots in one pass. Rake and till as deep as 4" to create the perfect seedbed. This unit separates rocks, tears up sod, and eliminates dirt clods for a truly professional finish.

FEATURES

- Direct-drive motor turns large 10" rotor
- Tungsten – carbide teeth
- Power angling (optional)
- Large solid rubber tires
- Optional box end plates (Wing Kit)

800.437.6912

ERSKINE[®]
ATTACHMENTS LLC

ERSKINE[®]

ATTACHMENTS LLC

www.erskineattachments.com

800.437.6912

SOIL CONDITIONER

SKID STEER ATTACHMENT



Floating connection on FSC models provides automatic leveling that follows contour of the ground.



Larger 10" rotor moves a higher volume of dirt than the competition.

Model	FSC72	FSC84	FSC96
Part Number	900534	900536	901382
Rotor Width	72"	84"	96"
Overall Width	79.5"	91.5"	103.5"
Angling	Manual 25°	Manual 25°	Manual 25°
Wheels/Tires	18" x 8.5"	18" x 8.5"	18" x 8.5"
Solid Rubber	Solid Rubber	Solid Rubber	1,300 lb.
Teeth	88 Carbide Tipped	104 Carbide Tipped	120 Carbide Tipped
Recommended Hyd. Flow	15 - 33 GPM	15 - 33 GPM	15 - 33 GPM
Mounting Plate	Universal	Universal	Universal
Operating Weight (FSC)	1,150 lb.	1,250 lb.	1,350 lb.

Options

Hydraulic Power Angling

Wing Kit

Pistol Grip Control Harness*

Loader Specific Wire Harness*

Factory Installed Couplers

*Applies to Hydraulic Model Only

800.437.6912

ERSKINE[®]

ATTACHMENTS LLC

ERSKINE[®]
ATTACHMENTS LLC

www.erskineattachments.com
800.437.6912

SOIL CONDITIONER

SKID STEER ATTACHMENT



Large **SOLID RUBBER TIRES** allow easier maneuverability over rough terrain

Large 10" rotor
DIRECT-DRIVE MOTOR gives higher production with lower maintenance



Optional:
Wire Harness for hydraulic models with attachment controls. Fits Cat/ASV (8-pin) and John Deere/New Holland/CASE/Bobcat (14-pin).



Optional:
Pistol Grip Control Harness is required if skid steer is NOT equipped with attachment control system. (Only needed when ordering hydraulic angling model).



The additional frame weight adds to its sturdy and durable design, and also adds weight for less vibration and more aggressive tilling.



We spiral our tungsten-carbide teeth around the rotor, this pattern helps to maintain consistent torque on the rotor at all times.

800.437.6912

ERSKINE[®]
ATTACHMENTS LLC