

**ERSKINE**<sup>®</sup>  
ATTACHMENTS LLC

www.erskineattachments.com  
800.437.6912

## VIBRATORY PACKER

SKID STEER ATTACHMENT

**PACK IT...**

Compact flatwork, trenches and asphalt patching jobs while moving forward or in reverse. Offset drum design compacts next to sidewalks, walls or curbs. Drum oscillation keeps the roller in contact with the surface on uneven terrain.

### FEATURES

- Offset drum design allows the right side of the roller to extend past the machine This is very useful when compacting next to sidewalks, walls, or curbs
- Durable one-piece drum for extra strength
- Dual-direction vibration motor permits compaction traveling in either direction
- Drum rubber isolation mounts reduce vibration transfer to loader and operator
- Drum oscillation permits compaction over uneven terrain
- Our universal attachment plates fit most skid steers
- Free drum oscillation keeps more of the drum in contact with the surface on uneven terrain - up to 15°
- 3/8" thick mono-piece drum.

**800.437.6912**

**ERSKINE**<sup>®</sup>  
ATTACHMENTS LLC



## VIBRATORY PACKER

### SKID STEER ATTACHMENT



Free drum oscillation keeps more of the drum in contact with the surface on uneven terrain - up to 15°



The hydraulic motor is coupled to an eccentric shaft which creates the required vibration.

Model	48" Smooth	48" Padded Foot	72" Smooth	72" Padded Foot
Part Number	900720	900721	900722	900723
Weight	1,390 lb.	1,480 lb.	1,720 lb.	1,870 lb.
Height	24"	27.5"	24"	27.5"
Width	60"	60"	84"	84"
Length	42"	42"	42"	42"
VPM	2,000 @ 18 GPM	2,000 @ 18 GPM	2,000 @ 18 GPM	2,000 @ 18 GPM
Flow Range	11 - 22 GPM	11 - 22 GPM	11 - 22 GPM	11 - 22 GPM
Dynamic Force	4,050 lb.	4,000 lb.	4,150 lb.	4,100 lb.
Amplitude	.08"	.07"	.06"	.05"
Compacting Energy	100 lb./in.	350 lb./in.	80 lb./in.	290 lb./in.

#### Options

Case Drain Coupler

Factory Installed Couplers

**ERSKINE**<sup>®</sup>  
ATTACHMENTS LLC

www.erskineattachments.com  
800.437.6912

## VIBRATORY PACKER

SKID STEER ATTACHMENT

Polyurethane 1/2" thick **ADJUSTABLE SCRAPER** keeps drum clean

**A-500 GRADE C STEEL DRUM**



**ADDITIONAL SCRAPER** for reverse compaction

**MASSIVE 3" ECCENTRIC SHAFT** inside the drum produces the high dynamic forces with greaseable heavy-duty bearings transferring the forces to the drum. Solid shaft running the full length of the drum is equipped with 4 greaseable bearings. Two heavy-duty spherical inner drum bearings handle any high forces transmitted by the eccentric shaft.



Padded foot model



800.437.6912

**ERSKINE**<sup>®</sup>  
ATTACHMENTS LLC